



 **Wilsonart[®]**

FURNITURE

OFFICES | EDUCATION | RESIDENTIAL | HOSPITALITY | RETAIL





OFFICES

The best surface, the best match and the best textured finishes in the industry.



SCRATCH RESISTANCE

DUST PROOF

0.8MM
THICKNESS

RICH
TEXTURES
and
SURFACES

STAIN RESISTANCE

EDUCATION

From lunch room countertops to gym locker rooms, Wilsonart has a surface that can solve your specific requirements.





HOSPITALITY

Wilsonart has brought unmatched Beauty, Design & Craftsmanship to countertops and walls.



BOILING WATER RESISTANCE

RADIANT HEAT
RESISTANT
210 SECONDS



RESIDENTIAL

WilsonArt makes more than just surfaces, WilsonArt creates the places where memories are made.





Why Wilsonart Laminate?

Did you know laminate is 70% paper? Regarded as the most environmentally friendly countertop surface.



LOW
WEAR & TEAR



RETAIL

Wilsonart® provides beautifully integrated, surface that is even approved for Food Contact.



LIGHT RESISTANCE



*Wilsonart surfaces are the perfect solution
for most of your needs*





MORE

DURABLE

MORE
LASTING

New Arrivals. New Textures.
New Product. Our designs
provide designers versatility in
commercial & residential
applications.

Wilsonart® FURNITURE

TECHNICAL DETAILS

| NEMA Test | Typical Wilsonart | NEMA Standard | ISO 4586-3 |
|---|----------------------------|------------------------------|------------------------------|
| Thickness | 1.22mm - 0.13mm | N/A | N/A |
| Appearance | No ABC def. | No ABC def. | N/A |
| Light Resistance | Slight effect | Slight effect | Slight effect |
| Cleanability (cycles) | 10 | 20 (max) | 10 |
| Stain Resistance Reagents 1-10 Reagents 11-18 | no effect Slight effect | no effect Moderate effect | no effect Moderate effect |
| Boiling Water Resistance | Slight effect | No effect | Slight effect |
| High Temperature Resistance | Slight effect | Slight effect | Slight effect |
| Impact Resistance | 65" (1651mm) | 50" (1270mm) | 31.5" (800mm) |
| Radiant Heat Resistance | 210 seconds | 125 sec | ≥ 200 sec |
| Dimensional Stability Machine Direct on Cross direct on | 0.3% 0.7% | 0.5% 0.9% | 1.1% 1.4% |
| Surface Wear Resistance | Meets or exceeds 400 | 400 (min) | 350 (min) |
| Formability | Not applicable | Not applicable | Not applicable |
| Blistering | Not applicable | Not applicable | Not applicable |



55-E/1, STREET 6, JAMI COMMERCIAL, PHASE VII, DHA
KARACHI, PAKISTAN 75500

 0335-1114455